# CW³ DragLink - Dynamic Checkweigher Systems

**Designed for Food & Packaging Industries**

Dynamic Checkweigher

## Product Highlights

- For dynamic weighing of end-of-line products including beverages, cans and jars up to 6Kg
- Complete system available with specification including BRC, IFS, & Retail compliance
- Approved systems to OIML R51 and MID (EC TAC)
- Automatic Mean Weight Correction to help meet weight legislation
- Brushless motors & proven conveyor components designed for reliable 24/7 operation



### Simple Operation with Colour Touchscreen

Icon driven full colour touchscreen control interface, including multilevel password access and data logged events to aid traceability






### Fast, Simple & Accurate Setup

Type in your product details, initiate setup, and pass a pack several times and the CW3 is automatically set-up and ready to use for average or mean weights



### Save Money, Reduce Product Give Away


Using a highly reliable loadcell technologie the CW3 gives you accurate readings whilst minimalising unnecessary product give away





### Switch Products in Seconds with a Library of Stored Products

Up to 500 product calibration details are stored in memory ready for fast product recall using multi-product menus

# Technical Specification





All Measurements in MM

| | |
|---|---|
| Weight Range (g) MID/R51 Approved | 50 - 6000 |
| Weight Range (g) Non - Approved | 20 - 6000 |
| Typical Accuracy (g) | 0.24 |
| Finish | 304 stainless steel |
| Line Height Options | 750,800,850,900,950mm +/- 50mm |
| Maximum Speed | 115m/min |
| Supply Voltages | 110 or 230V/1ph / N+E 50 or 60Hz |
| Air Supply | 5 to 8 Bar (10mm Outside Dia) 72-116 PSI |
| Operating Temperatures | 0-40$^0$C |
| IP Rating | IP65 |
| Belt Width (Infeed/ Outfeed) | 200/300mm (Model Dependent) |
| Belt Type (Infeed/ Outfeed) | PU Anti Static |
| Weigh Table | Nylatron GS 1/4 Chain x 3 |
| Reporting | Batch, Shift |
| Data Retrieval | Via USB, Ethernet, Enet, Tracs |

## Automatic Reject Options

The CW$^3$ is supplied as standard with two output signals suitable for triggering third-party reject systems. Alternatively, it can be specified with an automatic reject station (with retail compliance) with the following options:

- Pusher
- Diverter
- Air Blast






Loma Systems is a registered trademark of Illinois Tool Works Inc. (ITW). Other names, logos, icons and marks identifying our products and services referenced herein are trademarks of ITW and may not be used without the prior written permission of ITW. Other product and company names listed are trademarks or trade names of their respective companies. Copyright © 2016 Illinois Tool Works Inc. All rights reserved. All of the specifications shown in this document are subject to change without notice.